

**Finis**  
**series**<sup>®</sup>



# Quick Start Guide

QuickScan W5  
Wired Barcode Reader

## **I. Important - Warnings and Safety Instructions**

1. Do not place the Barcode Scanners near the heat sources such as fire, radiators, stoves, light candles and other apparatus that produces heat.
2. Use only those accessories supplied by Fingers.
3. It is recommended to refer all servicing to qualified personnel. Servicing is required when the Barcode Scanner has been damaged in any way. Any evidence of any attempt to open and/or alter the device, including any scratch, peeling, puncturing, or removal of any of the labels, will void the Limited Warranty.

## **II. In the box**

- 1 x QuickScan W5 Barcode Reader
- 1 x USB Cable
- 1 x Pin for Removing Cable
- 1 x Quick Start Guide
- 1 x Brand Note

## **III. Care and Maintenance**

1. Unplug the Barcode Scanner before cleaning it.
2. Use soft, damp cloth to clean the surface.
3. Do not use any chemicals, solvents, or cleaning solutions containing alcohol, ammonia or abrasives.
4. Do not allow any liquid to enter into any of the openings.

## IV. Connecting the Scanner



## V. Reading Techniques

1. The viewfinder projects an aiming beam that should be centered over the barcode. However, it can be tilted at any angle and in any direction for an effective read.
2. Hand hold the scanner over the barcode, pull the trigger and position the aiming beam on the barcode.
3. The aiming beam is smaller when scanner is placed closer to the barcode and larger when it is farther from the code.
4. Hold the scanner close to the smaller barcodes, and farther away from bigger barcodes to get a good read.
5. If the barcode is highly reflective (ex. Laminated sheets, glossy), you might be required to position the scanner at an angle in such a way the barcode can be read and scanned clearly.

# Standard Product Defaults

The following barcode resets all standard product default settings.

1 Factory Default



Please note that the default interface is USB-IHD.  
Example: Scan the Factory Default, USB-IHD and add suffice "Enter" barcodes as below.

1 Factory Default



2 Enter



# Scan Mode

Manual



Continuous



Automatic Flashing



# Auto-Induction

ON



OFF



# Buzzer

ON



LOW



OFF



HIGH



# Image Inverted

DIRECT



REVERSE



# Keyboard Language

USA



UK



French



# Suffix Setting

Enter



Enter & Line Feed



Cancel



# USB-COM, RS 232 Baud Rate Setting

4800



19200



9600



38400



57600



115200



# Barcode Setting

 Enable Code 39

 Disable EAN-8

 Disable Code 39

 Enable Code-93

 Enable UPC-A

 Disable Code-93

 Disable UPC-A

 Enable Code-128

 Enable UPC-E

 Disable Code-128

 Disable UPC-E

 Enable Codebar

 Enable EAN-13

 Disable Codebar

 Disable EAN-13

 Enable Interleaved 2 of 5

 Enable EAN-8

 Disable Interleaved 2 of 5

 Enable Industrial 25

 Disable Industrial 25

# Barcode Setting (Cont...)



Enable  
MSI



Disable  
Postcode  
25



Disable  
MSI



Enable  
Aviation  
25



Enable  
Plessey



Disable  
Aviation  
25



Disable  
Plessey



Enable GS1  
Omni-  
directional



Enable  
Code-11



Disable GS1  
Omni-  
directional



Disable  
Code-11



Enable  
GS1  
Limited



Enable  
Matrix  
2 of 5



Disable  
GS1  
Limited



Disable  
Matrix  
2 of 5



Enable  
Postcode  
25

## VI. Product Specifications

<b>General</b>	Type:	Wired
	Interface:	USB
	Indicators:	Beeper, LED
	Operation Mode:	Trigger
	Barcode Type Support:	All Standard 1D Barcodes
<b>Optical</b>	Light Source:	650 nm visible laser diode
	Scan Rate:	300 scans/sec
	Resolution:	4 mil
	Print Contrast Ratio:	35% @ UPC/EAN, 100%
	Depth of Field:	0-250 mm
<b>Electrical</b>	Input Voltage:	5 V $\pm$ 1%
	Working Current:	85 mA
	Standby Current:	36 mA
	Sleep Mode:	
<b>Physical</b>	Housing Material:	ABS+PC
	Cable Type:	USB (2 meters)
	Dimensions:	17.2 (H) x 8.3 (W) x 7 (L) cm
	Weight:	205 grams
	Colour:	Black
<b>Environment &amp; Safety Conformance</b>	Operating Temperature:	0°C – 50°C
	Storage Temperature:	-26°C ~ 60°C
	Operating Humidity:	5% – 85% RH (Non-condensing)
	Shock Resistance:	3.0 m drops



[fingers.co.in](http://fingers.co.in)

Ver.: 1.0.2

• Images shown may vary from actual product. • Specifications, features and appearance are subject to change without notice. • All logos, brands, trademarks and product names are properties of their respective owners. • Product warranty is governed by warranty terms mentioned on [www.fingers.co.in](http://www.fingers.co.in) • This product falls under e-waste (Management & Handling) Rules, 2011. For proper disposal method, visit our website [www.fingers.co.in](http://www.fingers.co.in)